

IDC - punchdown blocks

Technical Spec.:

Electrical:

- Voltage Rating: 250VDC
- Current Rating: 1,5A
- Contact Resistance: 10 mΩ max.
- Insulation Resistance: 1.000MΩ min. @ 500VDC
- Dielectric Strength: 1.000 VAC, 60Hz, 1min.

Mechanical:

- Housing Material: PC UL94V-0
- Contact Material: Phosphor Bronze with Silver or tin plating.
- Wire: AWG 24-26

Environmental:

- Storage Temperature: -20°C to +80°C and humidity up to 95%
- Operational 0°C to 70°C



PDB40	PDB80	PDB4A	PDB6A	PDB8A
-------	-------	-------	-------	-------

4 pole IDC terminal block with contacts 0° - straight



8 pole IDC terminal block with contacts 0° - straight



4 pole IDC terminal block with contacts 45°



6 pole IDC terminal block with contacts 45°



8 pole IDC terminal block with contacts 45°



PDBTH	PDB4H	PDB8H	PDB2S	PDB4S
-------	-------	-------	-------	-------

110 IDC Insert & Pull



4 pole 110 idc



8 pole 110 idc



2 pole stackable IDC



4 pole stackable IDC



Headquarters:

Rodheimer Strasse 25h
61191 Rosbach
Germany
Tel: +49 600 392058
Fax: +49 600 392056
Email: contact@inelcotech.com

European Head Office:

Premyslovska 4
13000 Praha-3
Czech Republic
Tel: +420 2 22726337
Fax: +420 2 22724901
Email: europe@inelcotech.com

Asia Head Office:

1206 New Victory House
93 Wing Lok Street, Central
Hongkong (SAR)
Tel: +852 (2668) 9626
Fax: +852 (3528) 5608
Email: asia@inelcotech.com