










INELCO
THE DISTINCTION



PRODUCT CATALOGUE
compu-shield® - USB

compu-shield® - USB 3.0		
USB A 3.0 - US3AP1	USB B 3.0 - US3BP1	USB A 3.0 SMT - US3AS1
		
USB B 3.0 DIP90 - US3BT1	USB A 3.0 DIP90 - US3AT1	USB A 3.0 SMT - US3AF1
		
compu-shield® - USB		
USB A - USBAP1	USB B - USBBP1	USB A - USBAP2
		
USB A - USBAS1	USB A - USBAF1	USB B - USBBP2
		
USB A DIP180 - USBAV1	USB A SMT - USBAS1	USB A DIP 90 V- USBAVX
		
USB B DIP 180 - USBBV1	USB B - USBBF1	USB B DIP 90 - USBBT1
		

compu-shield® - USB		
USB A - USB2T1	USB A - USB2T2	USB A DIP90 - USB2T1
		
USB A - USBB4T1	Mini USB 5Pin SMT- USBMS1	Mini USB 5Pin - USBMP1
		
Micro USB- USBUP1	Micro USB- USBUP2	Micro USB 5Pin SMT- USBUS1
		
compu-shield® - HDMI / IEEE		
HDMI 19Pin SMT - HDMIS1	HDMI 19Pin SMT - HDMIS2	IEEE 1394 6 Pin - IEEEF10
		
HDMI 19Pin - HDMIP1	HDMI 19Pin - HDMIP2	IEEE 1394 6 Pin - IEEEF1V
		

compu-shield® - USB Technical Data

Electrical:

Voltage Rating: 250VDC
 Current Rating: 1,5A
 Contact Resistance: 30 mΩ max.
 Insulation Resistance: 1.000MΩ min. @ 500VDC
 Dielectric Strength: 1.000 VAC, 60Hz, 1min.

Mechanical:

Housing Material: glass filled Polyester or high temp. UL94V-0, black
 Insert Material: high temp. UL94V-0
 Contact Material: phosphor bronze 0,35 mm thickness
 Shield Material: Copper Alloy 0,25mm thickness
 Storage Temperature: -40°C ... +85°C
 Operating Temperature: -20°C ... +85°C

compu-shield® - USB Part Numbers

XXXXYZ-GG

Type of Connector	XXXX	Style	Y	Z = Style Counting No.	Gold Thickness GG
USB Type A	USBA	Cable Plug	P		Flashgold GF
USB Type B	USBB	THR horizontal	T		3µ" Gold G1
USB 3.0 Type A	US3A	THR vertical	V		6µ" Gold G2
USB 3.0 Type B	US3B	SMT horizontal	S		15µ" Gold G3
Mini USB	USBM	SMT vertical	U		30µ" Gold G4
Micro USB	USBU	Fitting Style	F		
HDMI	HDMI				
IEEE 1394	IEEE				

Headquarters:
 Rodheimer Strasse 25h
 61191 Rosbach
 Germany
 Tel: +49 600 392058
 Fax: +49 600 392056
 Email: contact@inelcotech.com

European Head Office:
 Premyslovska 4
 13000 Praha-3
 Czech Republic
 Tel: +420 2 22726337
 Fax: +420 2 22724901
 Email: europe@inelcotech.com

Asia Head Office:
 1206 New Victory House
 93 Wing Lok Street, Central
 Hongkong (SAR)
 Tel: +852 (2668) 9626
 Fax: +852 (3528) 5608
 Email: asia@inelcotech.com